

15843

Dependent Resurvey of a Portion of the East Boundary,  
T. 29 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

A root hole, bears S. 20° E., 25 lks. dist., with a down fir alongside, 18 ins. diam., with healed blaze. This tree was remarked by Strickler.

and the remains of a bearing tree mkd. by Strickler

A root hole, bears S. 42½° W., 39 lks. dist., with a down fir alongside, 18 ins. diam., with healed blaze.

and new bearing trees

A fir, 17 ins. diam., bears S. 66½° E., 44 lks. dist., mkd. T29S R2W S6 BT.

A fir, 23 ins. diam., bears S. 27½° W., 58 lks. dist., mkd. T29S R3W S1 BT.

Land, mountainous.  
Soil, rock and clay loam.  
Timber, fir, cedar, madrone, hemlock, alder, and maple; undergrowth, hazel, arrowwood, Oregon grape, salal, rhododendron, and fern.

Dependent Resurvey of a Portion of the North Boundary,  
T. 29 S., R. 3 W., Willamette Meridian, Oregon

(Restoring the survey by William H. Byars,  
U. S. Deputy Surveyor, in 1881,  
and the retracement by William N. Gibb,  
U. S. Deputy Surveyor, in 1910)

From the cor. of Tps. 29 S., Rs. 2 and 3 W.

N. 87° 54' W., on the N. bdy. of sec. 1, marking and blazing the true line.

Ascend 30 ft. over NE. slope, through moderate timber and undergrowth.

5.50 Spur, slopes N. 15° W.; desc. 225 ft. over NW. slope.

30.45 Creek, course N. 30° W.; desc. 65 ft. over NW. slope.

41.73 The ¼ sec. cor. of sec. 1 only, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1960, monumented with an iron post, 1½ ins. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd.

T 28 S R 3 W  
N  
¼ cor S 1  
T 29 S R 3 W  
1960

from which the remains of the original bearing trees

A fir snag, 14 ins. diam., bears N. 38½° W., 10 lks. dist., with fragmentary scribe marks visible on opened blaze. (Record, N. 32° W.)

A decayed fir stump, 16 ins. diam., bears S. 60° E., 10 lks. dist., with scribe marks ¼ S visible on open blaze. (Record, S. 52° E.)