

Dependent Resurvey of a Portion of the North Boundary,
T. 29 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

and the remains of bearing trees mkd. by Byron

A cedar, 28 ins. diam., bears S. 43° E., 46 lks. dist., with fragmentary scribe marks visible on open double blaze.

A fir snag, 6 ins. diam., bears S. 67° W., 19 lks. dist., with healed double blaze.

and new bearing trees

A cedar, 15 ins. diam., bears S. 77½° E., 86 lks. dist., mkd. ¼ S1 BT.

A fir, 8 ins. diam., bears S. 26¾° W., 66½ lks. dist., mkd. ¼ S1 BT.

N. 89° 29' W., beginning new measurement.

Continue over nearly level land, through moderate timber and dense undergrowth.

0.81 From this point, the closing cor. of secs. 35 and 36, bears North, 0.07 chs. dist., perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1960, from which the remains of the original bearing trees:

A madrone, 18 ins. diam., bears N. 26° W., 38 lks. dist., with fragmentary scribe marks visible on open blaze.

and bearing trees mkd. by Byron

A fir, 11 ins. diam., bears N. 2° E., 58 lks. dist., with healed double blaze. This tree was remarked by Tracy, in 1966.

A fir, 15 ins. diam., bears N. 33° W., 33 lks. dist., with healed double blaze.

Corner is located in a pond, 1 ch. diam.

From the corner point, a witness corner established by Vernon R. Tracy, Deputy County Surveyor, in 1966, bears North, 45½ lks. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

	T 29 S	
	WIT COR	
	S 35 S 36	R
CC	T 29 S	3
	30 FT S	W
	TO COR	
	1966	

from which bearing trees mkd. by Tracy

A fir, 11 ins. diam., bears N. 3° E., 12½ lks. dist., with healed blaze.

A fir, 10 ins. diam., bears N. 70° W., 15 lks. dist., with fragmentary scribe marks visible on open blaze.

Descend 55 ft. over NW. slope.