

Dependent Resurvey of a Portion of the North Boundary,
T. 29 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
19.10	Gravelled road, 20 lks. wide, bears N. 20° E. and S. 55° W.
37.82	<p>The ¼ sec. cor. of sec. 2 only, perpetuated by James W. Byron, Deputy County Surveyor, in 1960, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;"> T 28 S R 3 W N ¼ COR S 2 T 29 S R 3 W 1960 </p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A sawed fir stump, 40 ins. diam., bears South, 8 lks. dist., with scribe marks ¼ S visible on bark.</p> <p>and the remains of bearing trees mkd. by Byron</p> <p style="padding-left: 40px;">A cedar, 35 ins. diam., bears S. 63° E., 12 lks. dist., with scribe marks N 1/4 S2 CS BT.</p> <p style="padding-left: 40px;">A cedar snag, 35 ins. diam., bears S. 2° W., 65½ lks. dist., with scribe marks N 1/4 S2 CS BT.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 1° W., 59 lks. dist., mkd. ¼ S2 BT.</p> <p>Land, mountainous. Soil, clay loam. Timber, fir, cedar, madrone, hemlock, alder, and maple; undergrowth, hazel, arrowwood, Oregon grape, poison oak, and fern.</p>
<p>Dependent Resurvey of a Portion of the Subdivisional Lines T. 29 S., R. 3 W., Willamette Meridian, Oregon</p>	
<p>(Restoring the survey by William H. Byars, U. S. Deputy Surveyor, in 1881)</p>	
	<p>From the cor. of secs. 13 and 24 only, on the E. bdy. of the Tp.</p> <p>N. 89° 07' W., bet. secs. 13 and 24, marking and blazing the true line.</p> <p>Descend 350 ft. over NW. slope, through heavy timber and dense undergrowth.</p>
15.50	Creek, 1 lk. wide, course N. 55° W.; asc. 35 ft. over N. slope.
17.50	Top of ascent, slopes N.; desc. 30 ft. over NW. slope.
18.925	<p>Point for the E 1/16 sec. cor. of secs. 13 and 24.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>