

15947

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 3 W., Willamette Meridian, Oregon

| CHAINS | |
|--------|---|
| | <p style="text-align: center;">E 1/16 $\frac{S\ 13}{S\ 24}$ 1976</p> <p>from which</p> <p>A fir, 25 ins. diam., bears N. 40½° E., 55 lks. dist., mkd. E 1/16 S13 BT.</p> <p>A fir, 35 ins. diam., bears S. 35° E., 46½ lks. dist., mkd. E 1/16 S24 BT.</p> <p>Descend 225 ft. over NW. slope.</p> |
| 29.40 | Creek, 2 lks. wide, course N. 30° W.; asc. 60 ft. over NE. slope. |
| 33.85 | Top of ascent, slopes N.; desc. 80 ft. over NW. slope. |
| 37.85 | Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner. |
| | Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. |
| | T 29 S R 3 W ¼ $\frac{S\ 13}{S\ 24}$ 1976 |
| | <p>from which</p> <p>A fir, 14 ins. diam., bears N. 13° W., 38½ lks. dist., mkd. ¼ S13 BT.</p> <p>A fir, 15 ins. diam., bears S. 3½° E., 22½ lks. dist., mkd. ¼ S24 BT.</p> <p>Descend 75 ft. over NW. slope.</p> |
| 39.95 | Creek, 2 lks. wide, course N. 5° E.; asc. 95 ft. over NE. slope. |
| 44.75 | Top of ascent, slopes N.; desc. 425 ft. over NW. slope. |
| 62.70 | Days Creek, 15 lks. wide, course S. 40° W.; asc. 40 ft. over SE. slope. |
| 72.85 | Gravelled road, 20 lks. wide, bears N. 20° E. and S. 30° W. |
| 75.70 | <p>The cor. of secs. 13, 14, 23, and 24, perpetuated by John H. Markham, Jr., RPE No. 2880, in 1957, monumented with a truck axle, 1 in. diam., firmly set, projecting 6 ins. above ground, with 4 in. flange, from which the remains of the original bearing trees:</p> <p>A root crown, bears N. 89° E., 23 lks. dist.</p> <p>A root hole, bears S. 58° E., 38 lks. dist., with a down fir alongside, 70 ins. diam., with fragmentary scribe marks visible on bark.</p> <p>and bearing trees mkd. by Markham</p> <p>A fir, 20 ins. diam., bears N. 87° E., 55 lks. dist., with healed double blaze.</p> |