

01001

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

A fir, 13 ins. diam., bears S. 85° E., 65 lks. dist., with healed double blaze.

An alder, 15 ins. diam., bears S. 51° W., 58 lks. dist., with fragmentary scribe marks visible on open blaze.

A hemlock, 23 ins. diam., bears S. 86° W., 50 lks. dist., with healed double blaze.

A maple, 15 ins. diam., bears N. 79° W., 32 lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W
S 14 | S 13
S 23 | S 24
1976

Deposit axle alongside iron post.

Land, mountainous.

Soil, clay loam.

Timber, fir, cedar, hemlock, alder, madrone, and maple; undergrowth, arrowwood, hazel, rhododendron, salal, Oregon grape, poison oak, and fern.

N. 0° 48' E., bet. secs. 13 and 14.

Ascend 325 ft. over S. slope, through scattered timber and dense undergrowth.

19.905 Point for the S 1/16 sec. cor. of secs. 13 and 14.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

S 1/16
S 14 | S 13
1976

from which

A fir, 15 ins. diam., bears S. 41° E., 48 lks. dist., mkd. S 1/16 S13 BT.

A fir, 6 ins. diam., bears S. 69° W., 21 lks. dist., mkd. S 1/16 S14 BT.

Ascend 5 ft. over S. slope.

20.30 Spur, slopes S. 70° E.; desc. 40 ft. over NE. slope.

23.00 Ravine, drains S. 45° E.; asc. 180 ft. over SE. slope.

35.30 Head of ravine, drains S. 35° E.; asc. 100 ft. over S. slope.

39.81 Point for the ¼ sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 3 W
¼
S 14 | S 13
1976