

15849

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 29 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

from which

A fir, 6 ins. diam., bears S. 66° E., 13 lks.  
dist., mkd. ¼ S13 BT.

A fir, 47 ins. diam., bears N. 41° W., 66 lks.  
dist., mkd. ¼ S14 BT.

Ascend 185 ft. over S. slope.

50.35 Spur, slopes S. 70° E.; desc. 105 ft. over NE. slope.

59.715 Point for the N 1/16 sec. cor. of secs. 13 and 14.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.  
in the ground, with brass cap mkd.

N 1/16  
S 14 | S 13  
1976

from which

A fir, 5 ins. diam., bears N. 68° E., 46½ lks.  
dist., mkd. X BT.

A fir stump, 40 ins. diam., bears S. 29° W., 36½  
lks. dist., mkd. N 1/16 S14 BT.

Descend 160 ft. over NE. slope.

65.50 Ravine, drains N. 50° E.; asc. 140 ft. over SE. slope.

70.30 Spur, slopes S. 75° E.; desc. 30 ft. over NE. slope.

71.80 Ravine, drains S. 60° E.; asc. 70 ft. over S. slope.

74.25 Spur, slopes S. 55° E.; desc. 5 ft. over NE. slope.

76.85 Ravine, drains S. 60° E.; asc. 10 ft. over SE. slope.

79.62 The cor. of secs. 11, 12, 13, and 14, perpetuated and  
recorded by James W. Byron, Deputy County Surveyor, in  
1957, monumented with an iron post, 1 in. diam., firmly  
set, projecting 10 ins. above ground, with brass cap mkd.

T 29 S  
S 11 | S 12  
S 14 | S 13  
R 3 W  
1957

from which the remains of the original bearing trees

A madrone, 21 ins. diam., bears N. 44½° E., 29  
lks. dist., with fragmentary scribe marks visible  
on opened blaze. (Record, N. 40° E.)

A madrone, 21 ins. diam., bears S. 60½° E., 8 lks.  
dist., no marks visible on open blaze.  
(Record, S. 55° E.)

A madrone, 28 ins. diam., bears S. 12½° W., 8 lks.  
dist., with fragmentary scribe marks visible  
on open double blaze. (Record, S. 25° W.,  
18 lks.)

A root hole, bears N. 24° W., 50 lks. dist.