

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

and bearing trees mkd. by Byron

A root hole, bears N. $70\frac{1}{2}^{\circ}$ E., 59 lks. dist., with a down fir alongside, 15 ins. diam., with scribe marks 3W S12 BT visible on open double blaze.

A cedar, 32 ins. diam., bears S. 37° E., $74\frac{1}{2}$ lks. dist., with scribe marks 29S R3W S13 CS BT visible on open double blaze.

A fir, 13 ins. diam., bears N. $47\frac{1}{2}^{\circ}$ W., 85 lks. dist., with fragmentary scribe marks visible on open double blaze.

and a new bearing tree

A fir, 9 ins. diam., bears N. 5° W., $42\frac{1}{2}$ lks. dist., mkd. T29S R3W S11 BT.

Land, mountainous.

Soil, clay loam.

Timber, fir, madrone, cedar, alder, and hemlock, undergrowth, arrowwood, poison oak, hazel, Oregon grape, and fern.

From the cor. of secs. 12 and 13 only, on the E. bdy. of the Tp.

S. $89^{\circ} 20'$ W., bet. secs. 12 and 13.

Ascend 15 ft. over SE. slope, through medium timber and dense undergrowth.

- 1.95 Top of ascent, slopes S.; desc. 50 ft. over SW. slope.
- 4.30 Ravine, drains S. 10° E.; asc. 10 ft. over SE. slope.
- 6.10 Ravine, drains S. 20° E.; asc. 100 ft. over SE. slope.
- 13.25 Dirt road, 20 lks. wide, bears N. 70° E. and S. 70° W.
- 17.30 Spur, slopes S. 10° E.; desc. 85 ft. over SW. slope.
- 20.00 Same dirt road, 20 lks. wide, bears N. 40° W. and S. 40° E.
- 20.27 Point for the E $\frac{1}{16}$ sec. cor. of secs. 12 and 13.
- Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
- E $\frac{1}{16}$ $\frac{S 12}{S 13}$
1976
- from which
- A fir, 6 ins. diam., bears N. $38\frac{1}{2}^{\circ}$ W., $10\frac{1}{2}$ lks. dist., mkd. E $\frac{1}{16}$ S12 BT.
- A fir, 14 ins. diam., bears S. 3° W., 120 lks. dist., mkd. E $\frac{1}{16}$ S13 BT.
- Descend 55 ft. over SW. slope.
- 23.30 Creek, 5 lks. wide, course S. 25° E.; asc. 215 ft. over SE. slope.