

15851

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 3 W., Willamette Meridian, Oregon

CHAINS
25.30

Same dirt road, 20 lks. wide, bears N. 20° W. and
S. 20° E.

38.35

Spur, slopes S. 10° E.; desc. 45 ft. over SW. slope.

40.54

The $\frac{1}{4}$ sec. cor. of secs. 12 and 13, perpetuated and re-
corded by Claude Kerr, RPE No. 2125, in 1960, further
perpetuated and recorded by James W. Byron, Deputy County
Surveyor, in 1962, monumented with an iron post, $1\frac{1}{2}$ ins.
diam., firmly set, projecting 10 ins. above ground, with
brass cap mkd.

T 29 S R
S 12 3
S 13 W
1962 $\frac{1}{4}$

from which the remains of the original bearing trees

A madrone, 14 ins. diam., bears N. 30 $\frac{1}{2}$ ° E., 16
lks. dist., with healed blaze. This tree was
remarked $\frac{1}{4}$ S BT on bark, by Kerr, in 1960.

A madrone stump, 15 ins. diam., bears S. 56° W.,
12 lks. dist., no marks visible.

and the remains of bearing trees mkd. by Kerr

A sawed fir stump, 15 ins. diam., bears N. 50° W.,
18 lks. dist., with healed blaze.

A sawed madrone stump, 11 ins. diam., bears
S. 18° E., 9 lks. dist., with healed blaze.

and a new bearing tree

A cedar, 15 ins. diam., bears S. 19° W., 25 lks.
dist., mkd. $\frac{1}{4}$ S13 BT.

N. 87° 37' W., beginning new measurement.

Descend 275 ft. over W. slope.

7.70

Creek, 3 lks. wide, course S.; asc. 265 ft. over E.
slope.

8.40

Dirt road, 20 lks. wide, bears N. 10° E. and S.

18.045

Point for the W 1/16 sec. cor. of secs. 12 and 13.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

W 1/16 S 12
S 13
1976

from which

A hemlock, 18 ins. diam., bears N. 11 $\frac{1}{2}$ ° E., 22 lks.
dist., mkd. W 1/16 S12 BT.

A fir, 15 ins. diam., bears S. 52 $\frac{1}{2}$ ° W., 28 lks.
dist., mkd. W 1/16 S13 BT.

Ascend 240 ft. over E. slope.