

123
15856Dependent Resurvey of a Portion of the East Boundary,
T. 29 S., R. 4 W., Willamette Meridian, OregonCHAINS
19.62

The N 1/16 sec. cor. of sec. 24 only, on the E. bdy. of the Tp., established and recorded by Edwin S. Woodford, Registered Engineer No. 622, in 1956, monumented with an iron pipe, $\frac{3}{4}$ in. diam., firmly set, projecting 6 ins. above ground, from which a bearing tree mkd. by Woodford:

A fir, 9 ins. diam., bears S. $1\frac{1}{2}^{\circ}$ E., $30\frac{1}{2}$ lks. dist., with scribe marks N 1/16 S24 622 visible on opened upper portion of double blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, directly over iron pipe, with brass cap mkd.

N 1/16 |
S 24 |
1967

from which new bearing trees

A fir, 11 ins. diam., bears S. $52\frac{1}{2}^{\circ}$ W., 107 lks. dist., mkd. N 1/16 S24 BT.

A fir, 6 ins. diam., bears N. 75° W., 148 lks. dist., mkd. N 1/16 S24 BT.

N. $1^{\circ} 28'$ E., beginning new measurement.

Ascend 45 ft. over NE. slope.

0.80 Dirt road, 10 lks. wide, bears NE. and SW.

2.20 Spur, slopes E.; desc. 40 ft. over NE. slope.

6.80 Bottom of descent, slopes SE.; asc. 75 ft. over S. slope, changing to SE. slope.

13.43 The cor. of secs. 18 and 19 only, on the W. bdy. of T. 29 S., R. 3 W., monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 29 S
S 18
S 19
R 4 W | R 3 W
1960
BLM

from which the remains of the original bearing trees

A decayed fir stump, 14 ins. diam., bears N. 10° E., 30 lks. dist., with scribe marks BT visible on opened blaze.

A fir snag, 40 ins. diam., bears S. 80° E., 28 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

and bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1960

A fir, 6 ins. diam., bears N. 76° E., 30 lks. dist., no marks visible on partially healed double blaze.