

15858

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A madrone snag, 26 ins. diam., bears N. 35° E., 62 lks. dist., no marks visible on decayed blaze.

A madrone snag, 20 ins. diam., bears S. 15° E., 13 lks. dist., no marks visible on decayed blaze.

A madrone root crown, size indeterminate, bears N. 70° W., 15 lks. dist., no marks visible.

and the remains of bearing trees mkd. by Evans

A sawed fir stump, 12 ins. diam., bears N. 27° E., 85 lks. dist., no marks visible.

A cedar, 24 ins. diam., bears S. 31½° E., 31 lks. dist., with scribe marks T29S S36 CS BT visible on partially healed blaze.

A fir, 30 ins. diam., bears S. 61½° W., 54½ lks. dist., with scribe marks T29S R4W S35 BT visible on bark blaze.

A sawed fir stump, 14 ins. diam., bears N. 8½° W., 71 lks. dist., no marks visible.

and bearing trees mkd. by James W. Byron, Deputy County Surveyor, in 1963

A madrone, 9 ins. diam., bears S. 75½° W., 78½ lks. dist., with scribe marks S35 T29S R4W CS BT visible on partially healed blaze.

A fir, 10 ins. diam., bears N. 46½° W., 17 lks. dist., with scribe marks S26 CS BT visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.

T 29	S R 4 W
S 26	S 25
S 35	S 36
1967	

from which a new bearing tree

A fir, 10 ins. diam., bears N. 19° E., 30½ lks. dist., mkd. T29S R4W S25 BT.

N. 3° 59' E., bet. secs. 25 and 26, marking and blazing the true line.

Ascend 35 ft. over SE. slope, through heavy timber and light undergrowth, along E. edge of logged area.

6.50 Ravine, drains S. 35° E.; asc. 190 ft. over SW. slope.

22.30 Spur ridge, bears N. 70° E. and S. 70° W.; desc. 155 ft. over N. slope.

28.65 Ravine, drains NW.; desc. 25 ft. over NW. slope.

32.80 Bottom of descent, slopes W.; asc. 55 ft. over SW. slope.