

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS
36.72

The $\frac{1}{4}$ sec. cor. of secs. 25 and 26, reestablished by proportionate measurement by Arthur R. Evans, Deputy County Surveyor, in 1949, monumented with an iron pipe, $1\frac{1}{4}$ ins. diam., firmly set, projecting 6 ins. above ground. There is no remaining evidence of the original corner; therefore, this position is accepted as the corner, from which the remains of bearing trees mkd. by Evans:

A madrone, 19 ins. diam., bears N. 41° E., 37 lks. dist., with scribe marks 29 R4W $\frac{1}{4}$ S25 CS BT visible on partially healed blaze.

A sawed fir stump, 18 ins. diam., bears S. $30\frac{1}{2}^\circ$ W., 17 lks. dist., with scribe marks T29S $\frac{1}{4}$ S35 CS BT visible on partially healed blaze.

and a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1963

A fir, 12 ins. diam., bears S. 16° W., 22 lks. dist., with illegible scribe marks visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.

T 29 S R 4 W
 $\frac{1}{4}$
S 26 | S 25
1967

Corner is located at the NE. cor. of logged area, edges bear S. and W.

N. $3^\circ 59'$ E., beginning new measurement.

Ascend 40 ft. over SW. slope.

3.25 Spur, slopes W.; desc. 220 ft. over NW. slope.

17.32 Point selected for the witness N 1/16 sec. cor. to secs. 25 and 26.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

N 1/16
↑
S 26 | S 25
W C
1967

from which

A cedar, 8 ins. diam., bears N. $64\frac{1}{4}^\circ$ E., 192 lks. dist., mkd. X BT.

A white fir, 8 ins. diam., bears N. $51\frac{1}{2}^\circ$ W., 143 lks. dist., mkd. X BT.

Descend 5 ft. over NW. slope.