

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

CO SURVEY OFF

T 29 S R 4 W

24 | sec.

25 | cor.

RE 2741

BLM

from which the remains of the original SW. bearing tree

A decayed fir stump, 14 ins. diam., bears S. $76\frac{1}{2}^{\circ}$ W.
15 lks. dist., with fragmentary scribe marks
visible on opened blaze.

and the remains of bearing trees mkd. by Arthur R. Evans,
Deputy County Surveyor, in 1949

A fir, 25 ins. diam., bears S. 45° E., 31 lks.
dist., with partially healed blaze.

A root hole, bears N. 70° W., 23 lks. dist., with
a down fir alongside, 25 ins. diam., with scribe
marks T29S R4W S24 CS BT visible on bark blaze.

and a bearing tree mkd. by James W. Byron, Deputy County
Surveyor, in 1962.

A fir, 7 ins. diam., bears N. $14\frac{3}{4}^{\circ}$ W., 35 lks.
dist., with healed double blaze.

and a bearing tree mkd. by Donald R. Beck, in 1964

A fir, 8 ins. diam., bears S. $57\frac{1}{2}^{\circ}$ W., 48 lks.
dist., with scribe marks T29S R4W S25 BT visible
on open blaze.

S. $76^{\circ} 17'$ W., bet. secs. 24 and 25.

Descend 15 ft. along N. slope, changing to NW. slope,
through heavy timber and dense undergrowth.

8.95 Creek, 2 lks. wide, course N. 35° E.; asc. 290 ft. over
general W. slope.

19.02 The E 1/16 sec. cor. of secs. 24 and 25, established by
Arthur R. Evans, Deputy County Surveyor, in 1949, monu-
mented with an iron pipe, $1\frac{1}{2}$ ins. diam., firmly set,
projecting 9 ins. above ground, from which bearing trees
mkd. by Evans:

A cedar, 12 ins. diam., bears N. $3\frac{3}{4}^{\circ}$ E., $38\frac{1}{2}$ lks.
dist., with healed blaze.

A madrone, 10 ins. diam., bears S. $28\frac{1}{2}^{\circ}$ W., 11
lks. dist., with scribe marks 1/16 S25 visible
on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

E 1/16 $\frac{S 24}{S 25}$
1967

Reset iron pipe alongside iron post.