

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 $\frac{S\ 24}{S\ 25}$ 1967</p> <hr/> <p>S. 76° 17' W., beginning new measurement.</p> <p>Ascend 3 ft. over SE. slope.</p>
1.00	Spur, slopes S. 10° W.; desc. 35 ft. over SW. slope.
3.00	Bottom of descent, slopes S. 25° W.; asc. 5 ft. over SE. slope.
5.15	Spur, slopes S. 10° W., also dirt road, 15 lks. wide, bears NE. and NW., in curve; desc. 50 ft. over SW. slope.
8.15	Dirt road, 15 lks. wide, bears N. 12° W. and S. 12° E.
9.00	Bottom of descent, slopes S. 20° E.; asc. 35 ft. over SE. slope.
12.00	Spur, slopes S. 15° E.; desc. 55 ft. over SW. slope.
14.65	Bottom of descent, drains S. 20° E.; asc. 35 ft. over SE. slope.
17.20	Spur, slopes S. 15° E.; desc. 30 ft. over SW. slope.
19.02	The cor. of secs. 23, 24, 25, and 26.
	<p>Land, mountainous. Soil, rocky clay. Timber, fir, oak, cedar, madrone, apple, yew, alder, and cascara; undergrowth, salal, fern, poison oak, Oregon grape, vine maple, and thimbleberry.</p> <hr/> <p>N. 9° 24' E., bet. secs. 23 and 24.</p> <p>Ascend 85 ft. over SW. slope, through heavy timber and dense undergrowth, along W. edge of logged area.</p>
3.70	Spur, slopes S. 35° E.; asc. 10 ft. over S. slope.
5.40	Ridge, bears N. 70° E. and W.; desc. 615 ft. over N. slope.
11.80	Abandoned dirt road, 15 lks. wide, bears NE. and SW.
36.98	<p>The ¼ sec. cor. of secs. 23 and 24, reestablished by proportionate measurement by M. B. Germond and F. C. Frear, Deputy County Surveyors, in 1918, monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 4 ins. above ground. There is no remaining evidence of the original corner; therefore, this position is accepted as the corner, from which the remains of bearing trees mkd. by Germond and Frear:</p> <p style="text-align: center;">A sawed fir stump, 31 ins. diam., bears S. 52½° E., 21 lks. dist., with scribe marks CS ¼ S BT visible on bark blaze.</p>