

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A fir, 32 ins. diam., bears N. 72½° W., 13½ lks. dist., with scribe marks CS ¼ S23 BT visible on bark blaze.

and a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1962

A white fir, 10 ins. diam., bears S. 65° E., 26 lks. dist., with scribe marks ¼ S24 CS BT visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.

*FO. OK 1-95 BY R. BROWN
M 121-38*

T 29 S R 4 W
S 23 | S 24
1967

N. 9° 24' E., beginning new measurement.

Descend 40 ft. over N. slope, across partially logged area.

- 3.00 Dry bed of creek, 3 lks. wide, drains NW.; asc. 2 ft. along W. slope.
- 4.00 Top of ascent, slopes NW.; desc. 90 ft. over N. slope.
- 10.85 South Myrtle Creek Road, paved, 30 lks. wide, bears N. 75° W. and S. 75° E.
- 11.35 Bottom of descent, enter valley bottom, edge bears N. 75° W. and S. 75° E.; desc. 5 ft. over gradual N. slope.
- 11.45 Wire fence, extends N. 75° W. and S. 75° E.
- 12.25 The cor. of wire fences extending N. 9½° E. and N. 75° W., bears East, about 9 lks. dist.; enter open field.
- 19.45 South Myrtle Creek, 30 lks. wide, course SW.; asc. 50 ft. over S. slope.
- 20.70 Abandoned gravelled road, 20 lks. wide, bears N. 65° E. and S. 70° W.
- 27.55 The cor. of wire fences extending E. and S. 9½° W., bears West, about 8 lks. dist., also leave valley bottom, edge bears E. and W.; asc. 320 ft. over steep S. slope.
- 36.52 The cor. of secs. 13, 14, 23, and 24, perpetuated and recorded by M. B. Germond and F. C. Frear, Deputy County Surveyors, in 1918; monumented with an iron pipe, 2 ins. diam., firmly set, projecting 5 ins. above ground, from which the remains of the original bearing trees:

A black oak stump, 36 ins. diam., bears N. 25° E., 5 lks. dist., no marks visible. (Record, N. 10° E.)