

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS					
	<p>A white oak, 50 ins. diam., bears S. <math>54\frac{1}{2}^{\circ}</math> W., <math>59\frac{1}{2}</math> lks. dist., with healed blaze. (Record, S. <math>74^{\circ}</math> W., 47 lks.)</p> <p>A black oak, 25 ins. diam., bears N. <math>74\frac{1}{2}^{\circ}</math> W., 54 lks. dist., with healed blaze. (Record, N. <math>76^{\circ}</math> W.)</p> <p>and a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1962</p> <p>A madrone, 6 ins. diam., bears N. <math>59\frac{1}{2}^{\circ}</math> E., 27 lks. dist., with scribe marks S13 CS BT visible on partially healed blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 29 S R 4 W</p> <table border="1" style="margin: auto;"> <tr> <td>S 14</td> <td>S 13</td> </tr> <tr> <td>S 23</td> <td>S 24</td> </tr> </table> <p>1967</p> </div> <p>No suitable tree available within limits in sec. 24.</p> <p>Reset iron pipe alongside iron post.</p> <p>Corner is located at the cor. of wire fences extending E., S., and W.</p> <p>Land, mountainous. Soil, rocky clay loam. Timber, fir, oak, cedar, madrone, yew, maple, dogwood, and cascara; undergrowth, fern, salal, poison oak, vine maple, Oregon grape, blackberry, thimbleberry, and hazel.</p>	S 14	S 13	S 23	S 24
S 14	S 13				
S 23	S 24				
	<p>From the cor. of secs. 13 and 24 only, on the E. bdy. of the Tp.</p> <p>S. <math>46^{\circ} 48'</math> W., bet. secs. 13 and 24.</p> <p>Descend 15 ft. over SW. slope, through heavy timber and dense undergrowth, along N. edge of logged area.</p>				
2.50	Ravine, drains E.; asc. 120 ft. over NE. slope.				
11.00	Spur, slopes S.; desc. 90 ft. over W. slope.				
17.54	<p>The E 1/16 sec. cor. of secs. 13 and 24, established by Edwin S. Woodford, Registered Engineer No. 622, in 1956, monumented with an iron pipe, <math>1\frac{1}{2}</math> ins. diam., firmly set, projecting 2 ins. above ground. This position is accepted as the corner, from which the remains of bearing trees mkd. by Woodford:</p> <p>A madrone, 25 ins. diam., bears N. <math>10\frac{1}{2}^{\circ}</math> E., 13 lks. dist., with scribe marks E 1/16 S13 622 BT visible on partially healed double blaze.</p> <p>A sawed fir stump, 10 ins. diam., bears South, 11 lks. dist., with scribe marks E 1/16 S24 622 BT visible on open double blaze.</p> <p>At the corner point</p>				