

15868

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

From the cor. of secs. 21, 22, 27, and 28, perpetuated and recorded by Ben B. Irving, Deputy County Surveyor, in 1948, from original evidence no longer in existence, and further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1956. This corner is accepted as the best available evidence of the original corner position, monumented with an iron pipe, 3/4 in. diam., firmly set, projecting 8 ins. above ground, from which a bearing tree described by Irving:

A fir, 48 ins. diam., bears S. 37 1/4° E., 61 lks. dist., with scribe marks S27 CS BT visible on bark blaze, and scribe marks T29S R4W S27 CS BT, by Irving, in 1948, visible on bark blaze along-side.

and bearing tree mkd. by Irving

A fir, 15 ins. diam., bears N. 70° E., 102 lks. dist., with healed blaze.

A white fir, 17 ins. diam., bears S. 35° W., 34 lks. dist., with healed blaze.

A fir, 43 ins. diam., bears N. 30 1/2° W., 102 lks. dist., with healed blaze.

and a bearing tree mkd. by Byron

A white fir, 17 ins. diam., bears S. 79 1/2° W., 36 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.

T 29 S R 4 W
S 21 | S 22
S 28 | S 27
1969

Corner is located at SE. cor. of logged area, edges bear N. and W.

N. 1° 10' E., bet. secs. 21 and 22.

Descend 35 ft. over NW. slope, through old logged area and medium undergrowth.

3.95 Spur, slopes N. 60° W.; desc. 75 ft. over N. slope.

6.45 Ravine, drains NW.; asc. 65 ft. over SW. slope.

10.55 Spur, slopes W.; desc. 100 ft. over NW. slope.

19.69 From this point, a local corner established by person(s) unknown, bears West, 0.38 chs. dist., monumented with a cedar post, 8 x 8 ins. square, firmly set, projecting 14 ins. above ground, with scribe marks S 1/16 CS S21 visible on W. face, and perpetuated and recorded by Ben B. Irving, Deputy County Surveyor, in 1948, with an iron pipe, firmly set alongside the cedar post, projecting 6 ins. above ground, from which bearing trees rescribed by Irving, in 1948: