

15870

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	Ascend 190 ft. over gentle S. slope.
48.25	South Myrtle Creek Road, paved, 30 lks. wide, bears N. 65° W. and S. 65° E.
62.95	Leave field, enter oak thicket, edge bears E. and W.
69.07	Intersect the N. bdy. of Donation Land Claim No. 38, and point for the crossing closing corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T 29 S R 4 W CCC S 21   S 22 C 38 1969
	from which
	A fir, 12 ins. diam., bears N. 58½° E., 61 lks. dist., mkd. T29S R4W S22 CCC BT.
	A fir, 17 ins. diam., bears N. 35½° W., 67 lks. dist., mkd. T29S R4W S21 CCC BT.
	From this point, the NW. cor. of Claim No. 38, and on the E. bdy. of Claim No. 39, bears N. 89° 51' W., 15.72 chs. dist., hereinafter described.
	Ascend 90 ft. over SE. slope.
69.15	Wire fence, extends E. and W.
73.60	Spur, slopes S. 75° W.; desc. 25 ft. along W. slope.
78.50	Point for the cor. of secs. 15, 16, 21, and 22, at proportionate distance based on the original Ford survey, latitudinally, and longitudinally based on Hathorn's record claim line survey ties to the cor. of secs. 14, 15, 22, and 23, and the cor. of secs. 15, 16, 21, and 22. This method places the corner in good correlation to the original NW. cor. of Donation Land Claim No. 38 and the original NE. cor. of Donation Land Claim No. 39; there is no remaining evidence of the original corner.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 29 S R 4 W S 16   S 15 S 21   S 22 1969
	from which
	A cedar, 7 ins. diam., bears N. 71½° E., 29 lks. dist., mkd. T29S R4W S15 BT.
	A cedar, 25 ins. diam., bears S. 26° E., 57½ lks. dist., mkd. T29S R4W S22 BT.
	A fir, 22 ins. diam., bears S. 36½° W., 106 lks. dist., mkd. T29S R4W S21 BT.
	A fir, 55 ins. diam., bears N. 21½° W., 118 lks. dist., mkd. T29S R4W S16 BT.