

15872

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.

T 29 S R 4 W
S 15 | S 14
S 22 | S 23
1969

from which a new bearing tree

A cedar, 6 ins. diam., bears S. 55° W., 143 lks. dist., mkd. T29S R4W S22 BT.

N. 88° 43' W., bet. secs. 15 and 22.

Ascend 125 ft. over SE. slope, through old logged area and heavy reproduction.

- 13.75 Spur, slopes S.; desc. 285 ft. over SW. slope.
- 24.30 Gravelled road, 15 lks. wide, bears N. and S.
- 25.55 Ben Branch Creek, 5 lks. wide, course S.; asc. 305 ft. over SE. slope.
- 27.50 Gravelled road, 15 lks. wide, bears N. and S., curving S. 25° E.
- 38.63 Point for the ¼ sec. cor. of secs. 15 and 22, at proportionate distance based on record ties of the Hathorn survey of the claim lines; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 4 W
¼ S 15
S 22
1969

from which

A fir, 11 ins. diam., bears N. 69¼° W., 67½ lks. dist., mkd. ¼ S15 BT.

A fir, 20 ins. diam., bears S. 39¼° W., 4 lks. dist., mkd. ¼ S22 BT.

From this point, an iron pipe, ½ in. diam., firmly set, projecting 6 ins. above ground, bears S. 84° 30' W., 1.03 chs. dist.

Ascend 30 ft. over SE. slope.

- 41.00 Top of ascent, slopes S.; desc. 140 ft. over SW. slope.
- 50.80 Draw, drains S.; asc. 110 ft. over E. slope.
- 55.95 Spur, slopes S.; desc. 145 ft. over SW. slope.
- 64.35 Draw, drains S.; asc. 110 ft. over SE. slope.
- 71.50 Spur, slopes S. 60° W.; desc. 95 ft. over W. slope.