

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS 77.26	<p>The cor. of secs. 15, 16, 21, and 22.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, oak, cedar, madrone, yew, maple, dogwood, and cascara; undergrowth, fern, salal, poison oak, vine maple, Oregon grape, blackberry, thimbleberry, and hazel.</p>
8.20	<p>N. 1° 02' E., bet. secs. 15 and 16.</p> <p>Ascend 45 ft. along W. slope, through old logged area and heavy reproduction.</p> <p>Draw, drains S. 70° W.; asc. 145 ft. over S. slope.</p>
13.50	<p>Spur, slopes S. 70° W.; asc. 115 ft. over broken SW. slope.</p>
29.10	<p>Creek, 4 lks. wide, course S. 15° W.; asc. 135 ft. over SE. slope.</p>
39.25	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16, at propor- tionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T 29 S R 4 W $\frac{1}{4}$ S 16 S 15 1969</p>
	<p>from which .</p> <p>A fir, 16 ins. diam., bears N. 62° E., 101 lks. dist., mkd. $\frac{1}{4}$ S15 BT.</p> <p>A cedar, 16 ins. diam., bears S. 20° W., 114 lks. dist., mkd. $\frac{1}{4}$ S16 BT.</p>
	<p>From this point, a local corner established by John H. Markham, Jr., Registered Engineer No. 2880, in 1964, bears S. 80° 49' E., 0.795 chs. dist., monumented with a truck axle, 1 in. diam., firmly set, projecting 4 ins. above ground, from which the remains of bearing trees mkd. by Markham:</p> <p>A fir, 16 ins. diam., bears N. 36$\frac{3}{4}$° E., 12 lks. dist., with scribe marks $\frac{1}{4}$ S15 BT visible on partially healed double blaze.</p> <p>A fir snag, 10 ins. diam., bears S. 84$\frac{3}{4}$° E., 13$\frac{1}{2}$ lks. dist., with scribe marks $\frac{1}{4}$ S15 BT visible on partially healed double blaze.</p> <p>A cedar, 20 ins. diam., bears S. 26° W., 65 lks. dist., with scribe marks $\frac{1}{4}$ S16 BT visible on partially healed double blaze.</p>
	<p>Ascend 330 ft. over SE. slope.</p>
58.875	<p>Point for the N 1/16 sec. cor. of secs. 15 and 16.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>