

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

N 1/16  
S 16 | S 15  
1969

from which

A fir, 14 ins. diam., bears N. 77° E., 38 lks.  
dist., mkd. N 1/16 S15 BT.

A fir, 13 ins. diam., bears N. 14° W., 112 lks.  
dist., mkd. N 1/16 S16 BT.

Ascend 100 ft. over SE. slope.

63.10 Ridge, bears N. 65° E. and S. 65° W.; desc. 200 ft. over  
NW. slope.

74.50 Spring seepage, 1 lk. wide, course NW.; desc. 15 ft.  
over NW. slope.

78.50 The cor. of secs. 9, 10, 15, and 16, at proportionate  
distance; there is no remaining evidence of the original  
corner.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T 29 S R 4 W  
S 9 | S 10  
S 16 | S 15  
1969

from which

A fir, 6 ins. diam., bears N. 39° E., 27 lks.  
dist., mkd. T29S R4W S10 BT.

A chinquapin, 6 ins. diam., bears S. 69½° E., 29½  
lks. dist., mkd. T29S R4W S15 BT on bark.

A fir, 34 ins. diam., bears S. 82° W., 53 lks.  
dist., mkd. T29S R4W S16 BT.

A madrone, 50 ins. diam., bears N. 22° W., 44 lks.  
dist., mkd. T29S R4W S9 BT.

From this point, a local corner established by John H.  
Markham, Jr., Registered Engineer No. 2880, in 1964,  
bears S. 83° 52' W., 0.525 chs. dist., monumented with  
an iron pipe, 1 in. diam., firmly set, projecting 10 ins.  
above ground, from which bearing trees mkd. by Markham:

A madrone, 50 ins. diam., bears N. 37½° E., 58  
lks. dist., with scribe marks S10 T29S R4W BT  
visible on bark.

A cedar, 13 ins. diam., bears S. 40° E., 49 lks.  
dist., with scribe marks S15 BT visible on  
open blaze.

A fir, 15 ins. diam., bears S. 20° W., 80 lks.  
dist., with illegible scribe marks visible on  
open blaze.

A fir, 42 ins. diam., bears N. 16° W., 61 lks.  
dist., with scribe marks S9 XX BT visible on  
bark blaze.