

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	T 29 S R 4 W $\frac{1}{4}$ S 9 S 10 1969
	N. 0° 10' E., beginning new measurement.
	Ascend 320 ft. over SW. slope.
13.60	Spur, slopes S. 30° E.; desc. 25 ft. over NE. slope.
22.40	Bottom of descent, slopes E.; asc. 180 ft. over SE. slope.
33.40	Ridge, bears N. 30° E. and SW.; desc. 40 ft. over NW. slope.
38.93	<p>The cor. of secs. 3, 4, 9, and 10, perpetuated and recorded by Claude Kerr, Registered Engineer No. 2125, in 1950, and subsequently perpetuated by John H. Markham, Jr., Registered Engineer No. 2880, in 1959, monumented with an iron pipe, $\frac{3}{4}$ in. diam., firmly set, projecting 10 ins. above ground, from which the remains of the original bearing trees:</p> <p>A fir, 29 ins. diam., bears N. 36° E., 30 lks. dist., with healed blaze, and rescribed by Claude Kerr, Registered Engineer No. 2125, in 1950, with scribe marks X $\frac{1}{4}$ BT visible on bark blaze.</p> <p>A shattered cedar, 36 ins. diam., bears S. 42° W., 17 lks. dist., no marks visible.</p> <p>and bearing trees mkd. by Markham</p> <p>A madrone, 22 ins. diam., bears N. 9$\frac{1}{2}$° E., 54$\frac{1}{2}$ lks. dist., with scribe marks S3 T29S R4W BT visible on bark.</p> <p>A black oak, 8 ins. diam., bears N. 72$\frac{1}{2}$° E., 43 lks. dist., with healed blaze.</p> <p>A madrone, 11 ins. diam., bears S. 30$\frac{1}{2}$° E., 7 lks. dist., with scribe marks S10 T29S R4W BT visible on bark.</p> <p>A fir, 10 ins. diam., bears S. 26$\frac{1}{2}$° E., 22 lks. dist., with healed blaze and scribe marks BT visible on bark.</p> <p>A madrone, 8 ins. diam., bears S. 73$\frac{1}{2}$° W., 35$\frac{1}{2}$ lks. dist., with illegible scribe marks visible on bark.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.</p>
	T 29 S R 4 W S 4 S 3 S 9 S 10 1969