

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 21 ins. diam., bears N. $51\frac{1}{4}^{\circ}$ E., 153 lks. dist., mkd. $\frac{1}{4}$ S21 BT.</p> <hr/> <p>N. $88^{\circ} 13'$ W., beginning new measurement.</p> <p>Descend 35 ft. over NW. slope.</p>
0.25	Dirt road, 10 lks. wide, bears NW. and SE.
1.90	Creek, 2 lks. wide, course NW.; asc. 35 ft. over NE. slope.
5.00	Top of ascent, slopes N.; desc. 145 ft. over NW. slope.
15.00	Dirt road, 15 lks. wide, bears N. 40° E. and S. 40° W., also bottom of descent, slopes NW.; asc. slightly over NE. slope.
18.20	Point for the W $1/16$ sec. cor. of secs. 21 and 28.
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>W $1/16$ $\frac{S\ 21}{S\ 28}$ 1969</p> </div> <p>from which</p> <p>A fir, 6 ins. diam., bears N. $32\frac{3}{4}^{\circ}$ E., $42\frac{1}{2}$ lks. dist., mkd. W $1/16$ S21 BT.</p> <p>A fir, 11 ins. diam., bears S. $72\frac{3}{4}^{\circ}$ E., $73\frac{1}{2}$ lks. dist., mkd. W $1/16$ S28 BT.</p> <p>Ascend 5 ft. over NE. slope.</p>
18.90	Spur, slopes N. 10° W.; desc. 55 ft. over NW. slope.
21.70	Draw, drains N. 10° W.; asc. 40 ft. over NE. slope.
25.75	Spur, slopes N. 20° W.; desc. 210 ft. over NW. slope.
36.40	<p>The cor. of secs. 20, 21, 28, and 29, perpetuated and recorded by Jack L. Sheppard, RLS No. 180, in 1955, from original evidence no longer in existence, and further perpetuated by James W. Byron, Deputy County Surveyor, in 1963, monumented with an iron pipe, 2 ins. diam., firmly set, protruding 8 ins. above ground. This corner is accepted as the best available evidence of the position of the original corner, from which bearing trees mkd. by Byron:</p> <p>A madrone, 8 ins. diam., bears N. 58° E., $10\frac{1}{2}$ lks. dist., with scribe marks S21 T29S R4W CS BT visible on partially healed double blaze.</p> <p>A madrone, 7 ins. diam., bears S. 8° E., $45\frac{1}{2}$ lks. dist., with scribe marks S28 CS BT visible on partially healed double blaze.</p> <p>A fir, 8 ins. diam., bears S. $73\frac{1}{2}^{\circ}$ W., 79 lks. dist., with healed double blaze.</p> <p>At the corner point</p>