

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 29 S R 4 W S 20   S 21 S 29   S 28 1969</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A madrone, 7 ins. diam., bears N. 15¼° W., 64 lks. dist., mkd. T29S R4W S20 BT.</p> <p style="padding-left: 40px;">Reset iron pipe alongside iron post.</p> <p>Corner is located at a cor. of fences, extending S. and W.</p> <p>Land, mountainous. Soil, rocky clay. Timber, fir, oak, cedar, madrone, yew, maple, dogwood, chinquapin, and cascara; undergrowth, fern, salal, poison oak, vine maple, Oregon grape, blackberry, thimbleberry, and hazel.</p>
	<p>N. 1° 02' E., bet. secs. 20 and 21.</p> <p>Descend 115 ft. over NW. slope, through heavy timber and dense undergrowth.</p>
11.80	Dry creek, 4 lks. wide, drains W.; asc. 10 ft. over SW. slope.
16.00	Top of ascent, slopes W.; desc. 45 ft. over NW. slope.
18.50	Creek, 2 lks. wide, course W.; asc. 5 ft. over nearly level land.
18.70	Wire fence, extends E. and W., also enter open field, edge bears same as fence.
19.75	<p>Point for the S 1/16 sec. cor. of secs. 20 and 21.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. below the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 20   S 21 1969</p> <p>from which</p> <p style="padding-left: 40px;">An ash, 21 ins. diam., bears S. 30¼° E., 133 lks. dist., mkd. S 1/16 S21 BT.</p> <p style="padding-left: 40px;">An ash, 22 ins. diam., bears S. 12° W., 136 lks. dist., mkd. S 1/16 S20 BT.</p> <p>Corner is located in open field; also top of ascent, slopes W.</p> <p>Descend 15 ft. over nearly level bottom land.</p>
24.00	Wire fence, extends E. and W.