

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

| | |
|-----------------|--|
| CHAINS 39.50 | <p>The ¼ sec. cor. of secs. 20 and 21, reestablished by proportionate measurement by W. H. Wood, Deputy County Surveyor, in 1925, and perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1968. There is no remaining evidence of the original corner; therefore, this position is accepted as the corner, monumented with an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T 29 S R 4 W ¼ S 20 S 21 1968</p> |
| | <p>from which bearing trees mkd. by Wood</p> |
| | <p style="padding-left: 40px;">An alder, 24 ins. diam., bears N. 32½° E., 49 lks. dist., no marks visible.</p> |
| | <p style="padding-left: 40px;">An alder, 25 ins. diam., bears N. 22° W., 49 lks. dist., with old axe marks visible.</p> |
| | <p>and a bearing tree mkd. by N. E. Richardson, Deputy County Surveyor, in 1945</p> |
| | <p style="padding-left: 40px;">A triple alder, 25 ins. diam., bears N. 70° E., 88 lks. dist., with scribe marks ¼ S21 CS BT visible on bark.</p> |
| | <p>and a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1959</p> |
| | <p style="padding-left: 40px;">A cedar, 24 ins. diam., bears S. 30¼° W., 216½ lks. dist., with healed double blaze.</p> |
| | <p>N. 0° 59' E., beginning new measurement.</p> |
| | <p>Descend 2 ft. over nearly level bottom land.</p> |
| 0.80 | <p>Left bank of South Myrtle Creek, bears N. 50° E. and S. 50° W., course S. 50° W.; thence across river.</p> |
| 2.90 | <p>Right bank of South Myrtle Creek, bears N. 50° E. and S. 50° W.; asc. 270 ft. over general S. slope.</p> |
| 4.30 | <p>Wire fence, extends NE. and SW.</p> |
| 5.80 | <p>Wire fence, extends E. and W.</p> |
| 6.90 | <p>Wire fence, extends N. 25° E. and SW.</p> |
| 7.70 | <p>South Myrtle Creek Road, paved, 30 lks. wide, bears N. 25° E. and SW., in curve.</p> |
| 9.00 | <p>Wire fence, extends N. 25° E. and SW.</p> |
| 12.60 | <p>Private driveway, gravelled, 15 lks. wide, bears NW. and SE.</p> |
| 13.00 | <p>Wire fence, extends NW. and SE.</p> |
| 20.50 | <p>Dirt road, 10 lks. wide, bears N. 70° W. and S. 70° E.</p> |
| 39.59 | <p>The cor. of secs. 16, 17, 20, and 21, perpetuated and recorded by W. H. Wood, Deputy County Surveyor, in 1925, monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 12 ins. above ground, from which the remains of the original bearing trees:</p> |