

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
	<p>from which</p> <p>A madrone, 15 ins. diam., bears N. 24° E., 15½ lks. dist., mkd. T29S R4W S16 CCC BT.</p> <p>A fir, 8 ins. diam., bears S. 21° E., 73½ lks. dist., mkd. T29S R4W S21 CCC BT.</p> <p>From this point, the NE. cor. of Claim No. 39, bears N. 0° 18' E., 5.34 chs. dist., hereinafter described.</p> <p>Corner is located on spur, slopes S. 20° W., also in fence, extends N. and S.</p> <p>Descend 140 ft. over SW. slope.</p>
23.45	Spur, slopes S. 55° W.; desc. 190 ft. over SW. slope.
29.35	Wire fence, extends N. 55° W. and S. 55° E., also enter open field, edge bears same as fence.
36.50	<p>Point for the ¼ sec. cor. of secs. 16 and 21, at proportionate distance based on record ties of the Hathorn survey of the claim lines; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 29 S R 4 W</p> <p>    S 16</p> <p>    S 21</p> <p>    1969</p> </div> <p style="text-align: right; font-style: italic;">FD. OK 8/93 B. SHAWER R.M. 3-79</p> <p>from which bearing trees mkd. by John H. Markham, Jr., Registered Engineer No. 2880, in 1964</p> <p>An oak, 11 ins. diam., bears N. 19½° E., 259 lks. dist., with healed double blaze.</p> <p>An oak, 15 ins. diam., bears N. 3° E., 268 lks. dist., with healed blaze.</p> <p>Markham's bearing trees were utilized because no other trees were available within limits.</p> <p>From this point, a local corner, established by John H. Markham, Jr., Registered Engineer No. 2880, in 1964, bears N. 79° 40' W., 1.07 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set flush with surface of the ground.</p> <p>Corner is located in an open field.</p> <p>Descend 5 ft. over nearly level land.</p>
37.40	Creek, 1 lk. wide, course S.; asc. 125 ft. over SE. slope.
49.10	Wire fence, extends N. 60° E. and S. 60° W., also leave open field, edge bears same as fence.
52.00	Top of ascent, slopes S.; desc. 85 ft. over SW. slope.
57.85	Enter open field, edge bears NW. and SE.
62.00	School Hollow Creek, 1 lk. wide, course SE.; asc. 225 ft. over NE. slope.