

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
31.40	School Hollow Creek, 2 lks. wide, course S. 55° W.; asc. 80 ft. over SE. slope.
35.50	Gravelled road, 15 lks. wide, bears N., curving NE. and S., curving SW.
36.96	<p>The ¼ sec. cor. of secs. 9 and 16, perpetuated and recorded by W. H. Wood, Deputy County Surveyor, in 1925, from original evidence no longer in existence, and further perpetuated and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1956, monumented with a solid steel shaft, 2 ins. diam., loosely set, projecting 15 ins. above ground, alongside of which is a burned cedar post, 2 ins. x 4 ins. square, loosely set, projecting 16 ins. above ground, with scribe marks S9 CS visible on N. face and S16 CS visible on S. face. This corner is accepted as the best available evidence of the original corner position, from which a bearing tree mkd. by A. Boyer, Deputy County Surveyor, in 1938:</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears N. 24° E., 372 lks. dist., with healed blaze.</p> <p>and bearing trees mkd. by Markham</p> <p style="padding-left: 40px;">An oak, 10 ins. diam., bears S. 4° E., 44 lks. dist., with healed blaze.</p> <p style="padding-left: 40px;">A madrone, 10 ins. diam., bears N. 53° W., 86½ lks. dist., with scribe marks ¼ S9 CS BT visible on open blaze. This tree was rescribed by James W. Byron, Deputy County Surveyor, in 1963.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over steel shaft, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T 29 S R 4 W</p> <p>¼ $\frac{S 9}{S 16}$</p> <p>1969</p> </div> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 14° W., 88 lks. dist., mkd. ¼ S16 BT.</p> <p style="padding-left: 40px;">Deposit cedar post alongside iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 50' W., beginning new measurement.</p> <p>Ascend 110 ft. over SE. slope.</p>
7.75	Spur, slopes S.; desc. 145 ft. over SW. slope.
17.90	Dirt road, 15 lks. wide, bears N. and S.
18.59	The W 1/16 sec. cor. of secs. 9 and 16, established by W. H. Wood, Deputy County Surveyor, in 1925, and perpetuated by person(s) unknown, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 14 ins. above ground. This position is accepted as the corner, from which bearing trees described by A. Boyer, Deputy County Surveyor, in 1938: