

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A root hole, bears S. $77\frac{1}{2}^{\circ}$ E., 34 lks. dist., with a down fir alongside, 27 ins. diam., with scribe marks 1/16 S16 CS BT visible on bark blaze.

A fir, 45 ins. diam., bears S. 13° E., 55 lks. dist., with scribe marks /16 S16 CS BT visible on bark blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.

W 1/16 $\frac{S\ 9}{S\ 16}$
1969

No suitable trees available in sec. 9.

N. $89^{\circ}\ 35'$ W., beginning new measurement.

Descend 2 ft. over SW. slope.

0.60 Ravine, drains S. 20° W.; asc. 600 ft. over SE. slope.

18.34 The cor. of secs. 9 and 16 only, perpetuated and recorded by W. H. Wood, Deputy County Surveyor, in 1925, from evidence no longer in existence, and further perpetuated and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1957, monumented with an iron bar, $\frac{1}{4}$ in. diam., firmly set, projecting 3 ins. above ground. This corner is accepted as the best available evidence of the original corner position, from which the remains of the bearing trees mkd. by Wood:

A fir snag, 7 ins. diam., bears N. 19° E., 40 lks. dist., with scribe marks S9 CS visible on partially healed blaze.

A fir, 17 ins. diam., bears S. 43° E., 44 lks. dist., with healed blaze.

A fir, 32 ins. diam., bears S. 9° W., 36 lks. dist., with healed blaze.

A fir stump, 16 ins. diam., bears N. $48\frac{1}{2}^{\circ}$ W., 28 lks. dist., no marks visible.

and the remains of bearing trees mkd. by Markham

A madrone, 25 ins. diam., bears S. 85° E., 37 lks. dist., with scribe marks T29S R4W S16 visible on bark and scribe marks CC S 6 CS BT by James W. Byron, Deputy County Surveyor, in 1963, visible on partially healed blaze.

A madrone, 30 ins. diam., bears S. $13\frac{1}{2}^{\circ}$ W., 138 lks. dist., with scribe marks T29S R4 S17 visible on partially healed blaze and BT visible on bark.

An oak snag, 12 ins. diam., bears S. 26° W., 58 lks. dist., with scribe marks S17 BT visible on partially healed blaze.

and a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1963.