

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A fir, 20 ins. diam., bears N.  $4\frac{1}{2}^{\circ}$  E., 144 lks. dist., with illegible scribe marks visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, directly over iron bar, with brass cap mkd.

$$\begin{array}{r} T\ 29\ S\ R\ 4\ W \\ S\ 17\ \left| \begin{array}{l} S\ 9 \\ S\ 16 \end{array} \right. \\ 1969 \end{array}$$

Land, mountainous.  
Soil, rocky clay.  
Timber, fir, oak, cedar, madrone, yew, maple, dogwood, and cascara; undergrowth, fern, salal, poison oak, vine maple, Oregon grape, blackberry, thimbleberry, and hazel.

N.  $7^{\circ} 21'$  E., along the W. bdy. of sec. 9.

Ascend slightly over SE. slope, through moderate timber and dense undergrowth.

5.24

The closing cor. of secs. 8 and 17, on the W. bdy. of sec. 9, perpetuated and recorded by John H. Markham, Jr., Registered Engineer No. 2880, in 1957, monumented with an iron pipe,  $\frac{3}{4}$  in. diam., firmly set, projecting 4 ins. above ground, from which the remains of the original bearing trees:

A fir, 25 ins. diam., bears S.  $29\frac{1}{2}^{\circ}$  W., 32 lks. dist., with healed blaze. (Record, S.  $33^{\circ}$  W.)

and bearing trees mkd. by Markham

A fir, 15 ins. diam., bears N.  $28\frac{1}{2}^{\circ}$  E., 80 lks. dist., with healed blaze and scribe marks BT visible on bark blaze.

A madrone, 28 ins. diam., bears N.  $47\frac{1}{2}^{\circ}$  E., 159 lks. dist., with scribe marks 29 R4 S9 visible on partially healed blaze.

A madrone, 37 ins. diam., bears S.  $42\frac{1}{2}^{\circ}$  E., 81 lks. dist., with decayed blaze, no marks visible.

and a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1963

A fir, 22 ins. diam., bears S.  $12\frac{1}{2}^{\circ}$  W., 70 lks. dist., with illegible scribe marks visible on open blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.

$$\begin{array}{r} T\ 29\ S\ R\ 4\ W \\ CC\ \frac{S\ 8}{S\ 17} \left| S\ 9 \right. \\ 1969 \end{array}$$