

15888

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS	
8.65	Ascend 45 ft. over SE. slope. Spur ridge, bears N. 10° E. and S. 10° W.; desc. 75 ft. over NW. slope.
18.25	Saddle, bears N. 15° E. and S. 15° W.; asc. 75 ft. over SW. slope.
23.33	Point for the S 1/16 sec. cor. of sec. 9 only. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> S 1/16 S 9 1969 </div> from which A fir, 9 ins. diam., bears N. 45° E., 64½ lks. dist., mkd. S 1/16 S9 BT. A fir, 13 ins. diam., bears S. 80° E., 23½ lks. dist., mkd. S 1/16 S9 BT.
30.95	Ascend 90 ft. over general S. slope. Ridge, bears N. 40° E. and S. 30° W.; desc. 235 ft. over NW. slope.
43.00	Spur, slopes N. 10° W.; desc. 70 ft. over NE. slope.
46.66	Point for the ¼ sec. cor. of secs. 8 and 9, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 29 S R 4 W ¼ S 8 S 9 1969 </div> from which A cedar, 13 ins. diam., bears N. 61° E., 24 lks. dist., mkd. ¼ S9 BT. A cedar, 12 ins. diam., bears S. 61° W., 12 lks. dist., mkd. ¼ S8 BT.
67.10	Descend 560 ft. over NE. slope. Creek, 4 lks. wide, course N. 35° W.; asc. 5 ft. over SW. slope.
67.24	Point for the N 1/16 sec. cor. of secs. 8 and 9. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> N 1/16 S 8 S 9 1969 </div> from which