

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A fir, 14 ins. diam., bears S. 60° E., 19 lks. dist., with healed blaze.

A madrone, 12 ins. diam., bears S. 6° W., 16½ lks. dist., with scribe marks ¼ S9 CS BT visible on bark.

A madrone snag, 10 ins. diam., bears N. 34½° W., 15 lks. dist., with illegible scribe marks visible on bark.

and a bearing tree mkd. by James W. Byron, Deputy County Surveyor, in 1963

A madrone, 9 ins. diam., bears N. 53° W., 13½ lks. dist., with scribe marks ¼ S4 CS BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.

T 29 S R 4 W
¼ S 4
S 9
1969

Corner is located on N. edge of spur, slopes N. 70° W.

N. 82° 07' W., beginning new measurement.

Descend 375 ft. over general W. slope.

16.07

The W 1/16 sec. cor. of secs. 4 and 9, established by John H. Markham, Jr., Registered Engineer No. 2880, in 1959, monumented with an iron pipe, ¾ in. diam., firmly set, projecting 8 ins. above ground. This position is accepted as the corner, from which bearing trees mkd. by Markham:

A fir, 6 ins. diam., bears S. 9° E., 14 lks. dist., with illegible scribe marks visible on partially healed blaze.

A fir, 30 ins. diam., bears S. 24° W., 35 lks. dist., with scribe marks L4 S9 BT visible on bark blaze.

A fir, 15 ins. diam., bears N. 31½° W., 11 lks. dist., with illegible scribe marks visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.

W 1/16 S 4
S 9
1969

N. 82° 34' W., beginning new measurement.

SEE CS 42/345-4 FOR
MARKHAM'S CORNER
ADDED 5/14/2024 JCDCSO