

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 4 W., Willamette Meridian, Oregon

CHAINS
72.16

The cor. of secs. 19, 20, 29, and 30, perpetuated and recorded by N. E. Richardson, Deputy County Surveyor, in 1945, and further perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1963, monumented with an iron spring and shackle, firmly set flush with the surface of the ground, with an iron pipe, 1 in. diam., firmly set alongside, projecting 12 ins. above ground, from which the remains of the original bearing trees:

A root hole, bears S. 60° W., 45 lks. dist., with a down black oak alongside, 18 ins. diam., with scribe marks BT visible on opened blaze.

A decayed and burned oak root crown, size indeterminate, bears S. 40° E., 60 lks. dist., no marks visible.

and the remains of bearing trees mkd. by Richardson

A fir, 36 ins. diam., bears N. 34° E., 10 lks. dist., with scribe marks S20 CS BT visible on bark.

A fir, 16 ins. diam., bears S. 51° E., 50 lks. dist., with scribe marks S29 CS BT visible on bark.

A sawed fir stump, 18 ins. diam., bears S. 74½° W., 30 lks. dist., with scribe marks BT visible on bark.

and bearing trees mkd. by Byron

A madrone, 14 ins. diam., bears S. 12° E., 57 lks. dist., with scribe marks T29S R4W S29 BT visible on open double blaze.

A fir, 8 ins. diam., bears S. 19° W., 44 lks. dist., with healed blaze.

A fir, 10 ins. diam., bears N. 82° W., 12 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, directly over inverted spring, with brass cap mkd.

T 29 S R 4 W			
S 19	S 20		
S 30	S 29		
1969			

Reset iron pipe alongside iron post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, oak, madrone, yew, maple, dogwood, pine, and cascara; undergrowth, fern, salal, poison oak, vine maple, Oregon grape, blackberry, thimbleberry, and hazel.

Dependent Resurvey of a Portion of Donation Land Claim
No. 37, T. 29 S., Rs. 3 and 4 W., Willamette Meridian,
Oregon