

Subdivision of Section 9, T. 29 S., R. 4 W.,  
Willamette Meridian, Oregon

CHAINS 12.70	Spur, slopes SE.; asc. 180 ft. over SE. slope.
21.51	<p>Point for the center S 1/16 sec. cor. of sec. 9.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C S 1/16   S 9 C 1969</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears S. 62° E., 9 lks. dist., mkd. CS 1/16 S9 BT.</p> <p style="padding-left: 40px;">A fir, 11 ins. diam., bears S. 89½° W., 53 lks. dist., mkd. CS 1/16 S9 BT.</p> <p>Ascend 275 ft. over SE. slope.</p>
37.60	<p>Ridge, bears N. 60° W. and E.; desc. 195 ft. over NW. slope.</p>
43.02	<p>Point for the center ¼ sec. cor. of sec. 9, at intersection with the E. and W. center line.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C ¼ S9 1969</p> <p>from which</p> <p style="padding-left: 40px;">A fir, 40 ins. diam., bears S. 8½° W., 109 lks. dist., mkd. C ¼ S9 BT.</p> <p style="padding-left: 40px;">A yew, 13 ins. diam., bears N. 30½° W., 93 lks. dist., mkd. C ¼ S9 BT.</p> <p>Descend 350 ft. over NW. slope.</p>
63.06	<p>Point for the center N 1/16 sec. cor. of sec. 9.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16   S 9 C 1969</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 17 ins. diam., bears N. 70½° E., 146 lks. dist., mkd. CN 1/16 S9 BT.</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears N. 20½° W., 172 lks. dist., mkd. CN 1/16 S9 BT.</p> <p>Corner is located in ravine, drains W.</p> <p>Ascend 70 ft. over SW. slope.</p>
68.95	Spur, slopes NW.; desc. 175 ft. over NW. slope.