

Subdivision of Section 9, T. 29 S., R. 4 W.,
Willamette Meridian, Oregon

CHAINS 74.75	Wet ravine, drains S. 80° W.; asc. 180 ft. over SW. slope.
82.50	Spur, slopes S. 65° W.; desc. 2 ft. over NW. slope.
83.10	The ¼ sec. cor. of secs. 4 and 9.
	From the ¼ sec. cor. of secs. 9 and 10. N. 84° 06' W., on the E. and W. center line of sec. 9. Descend 20 ft. over SW. slope, through moderate timber and dense undergrowth.
2.40	Creek, 2 lks. wide, course S.; asc. 160 ft. over SE. slope.
8.60	Spur, slopes S. 30° E.; desc. 30 ft. over SW. slope.
11.65	Ravine, drains SE.; asc. 150 ft. over SE. slope.
14.95	Spur, slopes S. 20° E.; asc. 10 ft. over SE. slope.
17.24	Point for the center E 1/16 sec. cor. of sec. 9. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> $C \frac{E \ 1/16}{S \ 9} C$ 1969 </div> from which A fir, 30 ins. diam., bears N. 30½° E., 74½ lks. dist., mkd. CE 1/16 S9 BT. A fir, 35 ins. diam., bears S. 60° E., 99 lks. dist., mkd. CE 1/16 S9 BT. Ascend 145 ft. over SE. slope.
24.90	Ridge, bears N. 40° E. and S. 40° W., also dirt road, 15 lks. wide, bears same; desc. 185 ft. over NW. slope.
34.48	The center ¼ sec. cor. of sec. 9. Descend 35 ft. over NW. slope.
35.50	Ravine, drains N. 10° E.; asc. 145 ft. over NE. slope.
41.95	Spur, slopes N. 20° W.; desc. 385 ft. over SW. slope.
51.57	Point for the center W 1/16 sec. cor. of sec. 9. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> $C \frac{W \ 1/16}{S \ 9} C$ 1969 </div> from which A maple, 13 ins. diam., bears N. 47° E., 76½ lks. dist., mkd. CW 1/16 S9 BT.