

15906

Subdivision of Section 9, T. 29 S., R. 4 W.,
Willamette Meridian, Oregon

CHAINS	
	SW 1/16 S9 1969
	from which
	A cedar, 8 ins. diam., bears N. 37½° W., 30 lks. dist., mkd. SW 1/16 S9 BT.
	A cedar, 18 ins. diam., bears S. 61½° E., 36½ lks. dist., mkd. SW 1/16 S9 BT.
	Ascend 395 ft. over SE. slope.
34.80	Ridge, bears N. 65° E. and S. 65° W.; desc. 360 ft. over NW. slope.
43.00	Ravine, drains NW.; asc. 30 ft. over SW. slope.
44.89	The center W 1/16 sec. cor. of sec. 9.
From the center S 1/16 sec. cor. of sec. 9.	
	N. 87° 11' W., on the E. and W. center line of the SW¼ of sec. 9.
	Ascend 75 ft. over SE. slope, through moderate timber and light undergrowth.
3.50	Spur, slopes SW.; desc. 345 ft. over W. slope.
15.25	Dirt road, 15 lks. wide, bears N. 30° E. and S. 30° W., also draw, drains S. 30° W.; asc. 20 ft. over SE. slope.
17.81	The SW 1/16 sec. cor. of sec. 9.
	Ascend 5 ft. over SE. slope.
18.60	Spur, slopes S.; desc. 15 ft. over SW. slope.
21.40	Draw, drains S.; asc. 420 ft. over NE. slope.
34.30	Spur, slopes S.; desc. 15 ft. over SW. slope.
35.52	The S 1/16 sec. cor. of sec. 9 only.
From the center W 1/16 sec. cor. of sec. 9.	
	N. 5° 38' E., on the N. and S. center line of the NW¼ of sec. 9.
	Ascend 70 ft. over SW. slope, through moderate timber and medium undergrowth.
5.95	Spur, slopes N. 60° W.; desc. 75 ft. over NW. slope.
10.20	Bottom of descent, slopes W.; asc. 55 ft. over SW. slope.
20.31	Point for the NW 1/16 sec. cor. of sec. 9, at intersection with the E. and W. center line of the NW¼.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.