

Subdivision of Section 9, T. 29 S., R. 4 W.,
Willamette Meridian, Oregon

CHAINS	
	NW 1/16 S9 1969
	from which
	A fir, 30 ins. diam., bears S. 45° E., 8 lks. dist., mkd. NW 1/16 S9 BT.
	A cedar, 13 ins. diam., bears S. 52° W., 45 lks. dist., mkd. NW 1/16 S9 BT.
	Ascend 5 ft. over SW. slope.
21.00	Spur, slopes N. 20° W.; desc. 460 ft. over NE. slope.
33.00	Dirt road, 15 lks. wide, bears NW. and E., in curve.
37.60	Creek, 2 lks. wide, course N. 75° W.; asc. 55 ft. over SW. slope.
40.72	The W 1/16 sec. cor. of secs. 4 and 9.
	From the center N 1/16 sec. cor. of sec. 9.
	N. 83° 16' W., on the E. and W. center line of the NW¼ of sec. 9.
	Descend 130 ft. over SW. slope, through moderate timber and light undergrowth.
8.55	Wet ravine, drains N.; asc. 255 ft. over NE. slope.
15.95	Spur, slopes N. 30° W.; desc. 15 ft. over SW. slope.
16.55	The NW 1/16 sec. cor. of sec. 9.
	Descend 470 ft. over SW. slope.
33.07	The N 1/16 sec. cor. of secs. 8 and 9.
	Subdivision of Section 21, T. 29 S., R. 4 W., Willamette Meridian, Oregon
	From the ¼ sec. cor. of secs. 21 and 28.
	N. 1° 04' E., on the N. and S. center line of sec. 21, marking and blazing the true line.
	Descend 5 ft. over NW. slope, through moderate timber and medium undergrowth.
0.45	Wet ravine, drains NW.; asc. 35 ft. along W. slope.
4.05	Spur, slopes N. 60° W.; desc. 175 ft. over NW. slope.
15.85	Ravine, drains NW.; desc. 15 ft. along W. slope.
18.10	Bottom of descent, slopes S. 65° W.; asc. 5 ft. over SW. slope.
19.68	Point for the center S 1/16 sec. cor. of sec. 21.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.