

15909

Subdivision of Section 21, T. 29 S., R. 4 W.,
Willamette Meridian, Oregon

CHAINS	
60.20	South Myrtle Creek, 40 lks. wide, course W. from S. 60° E.; asc. 40 ft. over bottom land.
61.30	South Myrtle Creek Road, paved, 30 lks. wide, bears S. 70° E. and W., in curve.
61.80	Wire fence, extends E. and W.
78.83	The ¼ sec. cor. of secs. 16 and 21.
	From the ¼ sec. cor. of secs. 21 and 22.
	N. 88° 01' W., on the E. and W. center line of sec. 21.
	Ascend 230 ft. over NE. slope, through heavy reproduction and dense undergrowth.
29.20	Spur, slopes N.; desc. 55 ft. over NW. slope.
31.55	Ravine, drains N.; asc. 175 ft. over NE. slope.
36.44	The center ¼ sec. cor. of sec. 21.
	Ascend 100 ft. over NE. slope.
39.00	Ridge, bears N. 30° W. and S. 30° E.; desc. 100 ft. over SW. slope.
49.40	Spur, slopes SW.; desc. 380 ft. over NW. slope.
61.75	Wire fence, extends N. and S., also enter open field, edge bears same as fence.
72.88	The ¼ sec. cor. of secs. 20 and 21.
	From the W 1/16 sec. cor. of secs. 21 and 28.
	N. 1° 02' E., on the N. and S. center line of the SW¼ of sec. 21.
	Descend 105 ft. over general N. slope, through heavy reproduction and medium undergrowth.
6.50	Bottom of descent, slopes NW.; asc. 20 ft. along W. slope.
10.15	Spur, slopes NW.; desc. 155 ft. over N. slope.
15.55	Wire fence, extends E. and W.
16.75	Creek, 2 lks. wide, course N. 65° W.; asc. 50 ft. over SW. slope.
17.55	Dirt road, 15 lks. wide, bears N. 70° W. and S. 70° E.
19.70	Point for the SW 1/16 sec. cor. of sec. 21, at intersection with the E. and W. center line of the SW¼.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	SW 1/16 S 21 1969
	from which