

15910

Subdivision of Section 21, T. 29 S., R. 4 W.,  
Willamette Meridian, Oregon

CHAINS	
	<p>A cedar, 6 ins. diam., bears N. 89° E., 109 lks. dist., mkd. SW 1/16 S21 BT.</p> <p>A twin oak, 11 ins. diam., bears S. 15½° W., 84 lks. dist., mkd. SW 1/16 S21 BT.</p> <p>Ascend 35 ft. over SW. slope.</p>
27.60	Top of ascent slopes W.; desc. 45 ft. over NW. slope.
32.30	Bottom of descent, slopes W.; asc. 130 ft. over SW. slope.
37.10	Spur, slopes SW.; desc. 80 ft. over NW. slope.
39.42	Intersect E. and W. center line of sec. 21, at a point from which the ¼ sec. cor. of secs. 20 and 21, bears N. 88° 01' W., 18.22 chs. dist. This point is not monumented.
40.07	The cor. of lots 2 and 3, on the S. bdy. of Donation Land Claim No. 39, hereinbefore described.
	<p>From the center S 1/16 sec. cor. of sec. 21.</p> <p>N. 88° 07' W., on the E. and W. center line of the SW¼ of sec. 21.</p> <p>Ascend 15 ft. over SW. slope, through heavy reproduction and medium undergrowth.</p>
1.70	Top of ascent, slopes S.; desc. 200 ft. over broken SW. slope.
16.45	Old board fence, extends N. and S.
18.23	The SW 1/16 sec. cor. of sec. 21.
	Descend 170 ft. over SW. slope.
25.10	Dirt road, 20 lks. wide, bears N. 40° W. and S. 50° E., curving to S. 70° E.
26.20	Same dirt road, 20 lks. wide, bears N. 30° E. and S. 30° W.
27.65	Wire fence, extends N. and S., also enter open field, edge bears same as fence.
36.49	The S 1/16 sec. cor. of secs. 20 and 21.
	<p>Subdivision of Section 24, T. 29 S., R. 4 W., Willamette Meridian, Oregon</p>
	<p>From the ¼ sec. cor. of secs. 24 and 25.</p> <p>N. 11° 29' E., on the N. and S. center line of sec. 24, marking and blazing the true line.</p> <p>Descend 655 ft. over N. slope, through scattering timber and dense undergrowth.</p>
19.50	South Myrtle Creek, 20 lks. wide, course N. 45° W.; asc. 230 ft. over S. slope.