

Subdivision of Section 24, T. 29 S., R. 4 W.,
Willamette Meridian, Oregon

<p>CHAINS 20.50</p>	<p>Paved road, 30 lks. wide, bears N. 45° W. and S. 45° E.</p>
<p>39.85</p>	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 24, at intersection with the E. and W. center line.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="display: flex; justify-content: space-between; align-items: flex-start;"> <div style="font-size: small; transform: rotate(-15deg);"> <p>FO. OK 1-95 BY R. BROWN M 121-28</p> </div> <div style="text-align: center;"> <p>T 29 S R 4 W C $\frac{1}{4}$ S 24 1977</p> </div> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. $50\frac{1}{2}$° E., $67\frac{1}{2}$ lks. dist., mkd. C $\frac{1}{4}$ S24 BT.</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears S. $60\frac{1}{2}$° W., $12\frac{1}{2}$ lks. dist., mkd. C $\frac{1}{4}$ S24 BT.</p> <p>From this point, a corner established by F. C. Frear, Deputy County Surveyor, in 1918, bears N. 66° 30' E., 0.23 chs. dist., monumented with an iron pipe, $\frac{3}{8}$ in. diam., firmly set, projecting 1 in. above ground, from which the remains of a bearing tree mkd. by Frear:</p> <p style="padding-left: 40px;">A decayed fir stump, 10 ins. diam., bears N. 33° W., 20 lks. dist., with fragmentary scribe marks visible on decayed blaze.</p> <p>Ascend 120 ft. over S. slope.</p>
<p>52.09</p>	<p>Point for the center N 1/16 sec. cor. of sec. 24.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-top: 10px;"> <p>C N 1/16 S 24 C 1977</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 5 ins. diam., bears N. $21\frac{1}{2}$° E., 38 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 7 ins. diam., bears N. $14\frac{1}{2}$° W., $31\frac{1}{2}$ lks. dist., mkd. CN 1/16 S24 BT.</p> <p>From this point, a corner established by F. C. Frear, Deputy County Surveyor, in 1918, bears N. 54° 30' E., 0.34 chs. dist., monumented with an iron pipe, $\frac{3}{8}$ in. diam., firmly set, projecting 2 ins. above ground.</p> <p>Ascend 140 ft. over S. slope.</p>
<p>64.33</p>	<p>The $\frac{1}{4}$ sec. cor. of secs. 13 and 24.</p> <hr/> <p>From the $\frac{1}{4}$ sec. cor. of sec. 24 only, on the E. bdy. of the Tp.</p> <p>S. 73° 23' W., on the E. and W. center line of sec. 24.</p> <p>Ascend 20 ft. over SE. slope, through light undergrowth.</p>