

15912

Subdivision of Section 24, T. 29 S., R. 4 W.,  
Willamette Meridian, Oregon

CHAINS  
0.035

Intersect the N. bdy. of Donation Land Claim No. 37.

2.60

Spur, slopes S.; desc. 65 ft. over broken SW. slope.

15.20

Spur, slopes S.; desc. 2 ft. over SW. slope.

15.38

Point for the center E 1/16 sec. cor. of sec. 24.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

C  $\frac{E\ 1/16}{S\ 24}$  C  
1977

from which

A cedar, 10 ins. diam., bears N. 23¼° E., 29 lks. dist., mkd. CE 1/16 S24 BT.

A cedar, 7 ins. diam., bears S. 4¼° W., 15½ lks. dist., mkd. CE 1/16 S24 BT.

Descend 145 ft. over SW. slope.

19.815

Intersect the W. bdy. of Donation Land Claim No. 37, and point for the crossing closing cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

C  $\frac{CCC}{S\ 24}$  C C37  
1977

from which

A cedar, 4 ins. diam., bears S. 52¼° W., 71½ lks. dist., mkd. X BT.

A cedar, 8 ins. diam., bears N. 20¼° W., 80½ lks. dist., mkd. T29S R4W S24 CCC BT.

From this point, a corner of which I have no record, bears N. 69° 45' E., 0.24 chs. dist., monumented with an iron pipe, 2 ins. diam., firmly set, projecting 1 in. above ground.

From this same point, the NW. cor. of Claim No. 37, bears N. 0° 09' E., 5.68 chs. dist.

Descend 30 ft. over SW. slope.

20.10

Dirt road, 15 lks. wide, bears N. 10° E. and S. 10° W.

20.85

Adams Creek, 5 lks. wide, course S.; asc. 85 ft. over SE. slope.

25.80

Spur, slopes S. 20° E.; desc. 35 ft. over SW. slope.

30.76

The center ¼ sec. cor. of sec. 24.

Descend 120 ft. over SW. slope.

51.50

Paved road, 30 lks. wide, bears N. 40° W. and S. 40° E.