

Subdivision of Section 24, T. 29 S., R. 4 W.,
Willamette Meridian, Oregon

<p>CHAINS 54.80</p>	<p>South Myrtle Creek, 10 lks. wide, course N. 40° W.; asc. 65 ft. over NE. slope.</p>
<p>68.45</p>	<p>Spur, slopes N.; desc. 20 ft. over W. slope.</p>
<p>71.32</p>	<p>The ¼ sec. cor. of secs. 23 and 24.</p>
<hr/>	
	<p>From the center E 1/16 sec. cor. of sec. 24.</p>
	<p>N. 5° 20' E., on the N. and S. center line of the NE¼ of sec. 24.</p>
	<p>Ascend 10 ft. over SW. slope, through light undergrowth.</p>
<p>4.425</p>	<p>Intersect the N. bdy. of Donation Land Claim No. 37, and point for the crossing closing cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>E CCC S 24 E C 37 1977</p> </div> <p>from which</p> <p>A fir, 10 ins. diam., bears N. 17° E., 41 lks. dist., mkd. T29S R4W S24 CCC BT.</p> <p>A cedar, 18 ins. diam., bears N. 51° W., 32½ lks. dist., mkd. T29S R4W S24 CCC BT.</p> <p>From this point, a corner established and recorded by Edwin S. Woodford, Registered Engineer, No. 622, in 1956, bears N. 55° 30' W., 0.095 chs. dist., monumented with an iron pipe, 1½ ins. diam., firmly set, projecting 2 ins. above ground, from which bearing trees mkd. by Woodford:</p> <p>A cedar, 13 ins. diam., bears S. 40¼° W., 8½ lks. dist., with fragmentary scribe marks visible on open blaze.</p> <p>A cedar, 18 ins. diam., bears S. 84° W., 27 lks. dist., with healed blaze.</p> <p>From this same point, the NW. cor. of Claim No. 37, bears N. 89° 54' W., 4.65 chs. dist.</p> <p>Descend 65 ft. over NW. slope.</p>
<p>12.50</p>	<p>Bottom of descent, slopes W.; asc. 10 ft. over SW. slope.</p>
<p>15.885</p>	<p>Point for the NE 1/16 sec. cor. of sec. 24, at intersection with the E. and W. center line of the NE¼.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>NE 1/16 S 24 1977</p> </div> <p>from which</p>