

15917

## T. 26 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and subdivisional lines of section 9, and a segregation survey of certain lands in the SE $\frac{1}{4}$  of section 9, township 26 south, range 3 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey, is as follows:

A portion of the subdivisional lines was surveyed by Addison R. Flint, in 1855.

A portion of the subdivisional lines was surveyed by William H. Byars, in 1877.

The boundaries of section 9 were resurveyed, section 9 was subdivided, the North Umpqua River was meandered in the SE $\frac{1}{4}$ SW $\frac{1}{4}$  section 9, and a power site reserve was surveyed by Fred Mensch, in 1924.

A portion of the subdivisional lines was resurveyed by C. Albert White, Donald R. Beck, and Patrick J. Reynolds, in 1962-63.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated September 5, 1972, for Group Number 796, Oregon.

The directions of the lines were determined by deflection angles turned from azimuths obtained by direct solar observations.

Preliminary to the resurvey, the lines of the previous surveys were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions, based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. All lines not forming closures were measured twice. Only those lines bounding or crossing public lands were blazed.

The geographic position of the corner of sections 9, 10, 15, and 16, as scaled from the Glide, Oregon, quadrangle map, published by the United States Geological Survey, in 1954, is as follows:

Latitude 43° 18.9' N. Longitude 123° 02.9' W.

The mean magnetic declination is 19° 45' E.

Dependent Resurvey of a Portion of the Subdivisional Lines  
T. 26 S., R. 3 W., Willamette Meridian, Oregon

(Restoring the survey by Addison R. Flint,  
U. S. Deputy Surveyor, in 1855,  
and the resurvey by Fred Mensch,  
U. S. Cadastral Engineer, in 1924)

Beginning at the cor. of secs. 9, 10, 15, and 16, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.