

Dependent Resurvey, Portion of Subdivisional Lines,
T. 26 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

T 26 S R 3 W
S 9 | S 10
S 16 | S 15
1924

from which bearing trees mkd. by G. G. Stewart, Deputy
County Surveyor, in 1922

A sawed fir stump, 42 ins. diam., bears S. 8° W.,
90 lks. dist., no marks visible.

A root hole, bears N. 40° W., 93 lks. dist., with
a down fir alongside, 40 ins. diam., with
fragmentary scribe marks visible on opened blaze.

and bearing trees mkd. by White, Beck, and Reynolds

A fir, 12 ins. diam., bears N. 16° E., 23 lks.
dist., with healed blaze. (Record, N. 21° E.)

A fir, 35 ins. diam., bears S. 35° E., 66 lks.
dist., with scribe marks T26S R3W S visible on
partially healed blaze. (Record, S. 30° E.)

A cedar, 19 ins. diam., bears S. 46° W., 238 lks.
dist., with healed blaze. (Record, S. 51½° W.)

A fir, 12 ins. diam., bears N. 25° W., 27 lks.
dist., with healed blaze. (Record, N. 19½° W.)

N. 3° 44' W., bet. secs. 9 and 10.

Ascend 110 ft. over SE. slope, through heavy timber and
light undergrowth.

12.75 Spur, slopes N. 80° E.; desc. 500 ft. over N. slope.

23.20 Leave heavy timber, edge bears E. and W.; continue
through moderate timber and light undergrowth.

24.95 Wire fence, bears N. 80° E. and S. 80° W.

35.30 Gravelled road, 20 lks. wide, bears N. 80° E. and
S. 80° W.

35.75 Point for angle point No. 19, 100 ft. normal dist. from
the mean high water line on the left bank of the North
Umpqua River.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, and in a mound of stone, 2 ft. base, to
top, with brass cap mkd.

AP 19
T 26 S | R 3 W
1972

from which

A fir, 10 ins. diam., bears North, 47 lks. dist.,
mkd. AP19 S9 BT.

A fir, 8 ins. diam., bears N. 29° W., 71 lks.
dist., mkd. AP19 S9 BT.

Descend 10 ft. over N. slope.