

15919

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 26 S., R. 3 W., Willamette Meridian, Oregon

CHAINS	
35.88	The initial point for the Clara Wood Homesites survey, established and recorded by Arthur Boyer, Registered Engineer No. 1581, in 1942, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 8 ins. above ground.
37.28	Point for a witness point on the line bet. secs. 9 and 10.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">W P S 9   S 10 1972</p>
	from which
	A fir, 10 ins. diam., bears S. 56° E., 48 lks. dist., mkd. WP S10 BT.
	A fir, 8 ins. diam., bears S. 65° W., 14 lks. dist., mkd. WP S9 BT.
	Descend 30 ft. over N. slope.
37.40	Intersect the mean high water line on the left bank of the North Umpqua River, bears N. 65° W. and S. 65° E.; river courses N. 65° W.
	Thence across river.
41.55	Right bank of North Umpqua River, bears same; asc. 10 ft. over S. slope.
41.74	The ¼ sec. cor. of secs. 9 and 10, determined from the remains of the original bearing trees:
	A white oak, 20 ins. diam., bears S. 84½° E., 100 lks. dist., no marks visible on decayed open blaze.
	A decayed black oak stump, 14 ins. diam., bears N. 54° W., 79 lks. dist., no marks visible.
	and a bearing tree mkd. by Mensch
	A fir, 15 ins. diam., bears N. 73° W., 19 lks. dist., with fragmentary scribe marks visible on opened blaze. (Record, N. 63° W.)
	At the corner point
	Seat a brass tablet, 3½ ins. diam., 3½ ins. stem, in a drill hole, in solid bedrock, with top mkd.
	<p style="text-align: center;">T 26 S R 3 W ¼ S 9   S 10 1972</p>