

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 26 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

From the corner point, a witness cor. to the 1/4 sec. cor. of secs. 9 and 10, bears North, 0.530 chs. dist., established and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1966, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE  
T 26 S R 3 W  
WC 1/4 S 9 | S 10  
35 ft. to corner  
1966

from which bearing trees mkd. by Tracy

A fir, 17 ins. diam., bears S. 80° E., 35 lks. dist., with healed blaze.


A fir, 10 ins. diam., bears S. 34° W., 12 lks. dist., with healed blaze.

Land, mountainous.  
Soil, rocky clay loam.  
Timber, fir, hemlock, cedar, maple, alder, madrone, oak, and chinquapin; undergrowth, vine maple, salal, fern, blackberry, hazel, and poison oak.

Dependent Resurvey of a Portion of the  
Subdivisional Lines of Section 9,  
T. 26 S., R. 3 W., Willamette Meridian, Oregon

(Restoring the survey by Fred Mensch,  
U. S. Cadastral Engineer, in 1924)

Beginning at the special meander cor. established in 1924 at the intersection of the right bank of the North Umpqua River with the N. and S. center line of sec. 9, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.



from which the original bearing trees

A fir, 13 ins. diam., bears S. 83° W., 57 lks. dist., with healed blaze.

A fir, 24 ins. diam., bears N. 9° W., 51 lks. dist., with healed blaze.

N. 0° 56' W., on the N. and S. center line of sec. 9.

Ascend 15 ft. over S. slope, through scattered timber and light undergrowth.

1.70 Center line, North Umpqua Highway, 40 lks. wide, bears NE. and SW.