

15921


Dependent Resurvey of a Portion of the
Subdivisional Lines of Section 9,
T. 26 S., R. 3 W., Willamette Meridian, Oregon

CHAINS
2.07

Point for angle point No. 1, at proportionate distance;
there is no remaining evidence of the original corner.

Set a brass tablet, $3\frac{1}{2}$ ins. diam., $3\frac{1}{2}$ ins. stem, in a
drill hole, in asphalt, with top mkd.

T 26 S R 3 W



from which

A fir, 20 ins. diam., bears S. 15° E., 135 lks.
dist., mkd. AP1 S9 BT.

No other suitable trees available within limits.

Thence over level ground.

2.88

The center S $1/16$ sec. cor. of sec. 9, monumented with
an iron post, 1 in. diam., firmly set, projecting 10 ins.
above ground, with brass cap mkd.

C
S $1/16$ | S 9
C
1924

from which the original bearing trees

A cedar, 24 ins. diam., bears N. 50° E., 8 lks.
dist., with healed blaze.

A fir, 10 ins. diam., bears S. $0^{\circ} 30'$ W., 44 lks.
dist., with healed blaze.

From the $\frac{1}{2}$ sec. cor. of secs. 9 and 10.

N. $89^{\circ} 33'$ W., on the E. and W. center line of sec. 9.

Descend 20 ft. over SW. slope.

0.65

Right bank of North Umpqua River, bears N. 65° W. and
S. 65° E., course N. 65° W.; thence across river.

10.74

Intersect the mean high water line on the left bank of
the North Umpqua River, bears N. 65° W. and S. 65° E.

11.64

Point for a witness point on the E. and W. center line
of sec. 9.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins.
in the ground, and in a mound of stone, 2 ft. base, to
top, with brass cap mkd.

W P
S
C — C
9
1972

from which