

Dependent Resurvey of a Portion of the
Subdivisional Lines of Section 9,
T. 26 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

A cedar, 15 ins. diam., bears S. 28° E., 51 lks.
dist., mkd. WP S9 BT.

A fir, 17 ins. diam., bears S. 57° W., 27 lks.
dist., mkd. WP S9 BT.

Ascend 30 ft. over NE. slope.

14.35 Spur, slopes N.; desc. 5 ft. over NW. slope.

14.40 Point for a witness point on the E. and W. center line
of sec. 9, on the left bank of the North Umpqua River,
bears N. 35° E. and S. 35° W., course S. 35° W.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, and in a mound of stone, 2 ft. base, to
top, with brass cap mkd.

W P
S
C — 9 — C
1972

from which

A fir, 10 ins. diam., bears S. 38° E., 29 lks.
dist., mkd. WP S9 BT.

A fir, 20 ins. diam., bears S. 25° W., 52 lks.
dist., mkd. WP S9 BT.

Thence across river.

22.51 Point for a witness point on the E. and W. center line
of sec. 9, on the right bank of the North Umpqua River,
bears N. 35° E. and S. 35° W.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.
in the ground, and in a mound of stone, 2 ft. base, to
top, with brass cap mkd.

W P
S
C — 9 — C
1972

from which

A cedar, 5 ins. diam., bears S. 87° W., 62 lks.
dist., mkd. WP S9 BT.

No other suitable trees available within limits.

Ascend 20 ft. over SE. slope.

24.43 Point for angle point No. 1, 100 ft. normal dist. from
the mean high water line on the right bank of the North
Umpqua River.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins.
in the ground, and in a mound of stone, 2 ft. base, to
top, with brass cap mkd.

T 26 S R 3 W
S 9
C — AP 1 — C
1972