


15925

Segregation Survey of Certain Lands in SE $\frac{1}{4}$, Section 9,
T. 26 S., R. 3 W., Willamette Meridian, Oregon

CHAINS
2.57

Angle point No. 1, on the N. and S. center line of sec. 9, hereinbefore described.

From angle point No. 7, on the N. and S. center line of sec. 9, established by Mensch in 1924, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.



from which the original bearing tree

A yew, 18 ins. diam., bears S. 84° W., 42 lks. dist., with healed blaze.

Thence


N. 45° 40' E., parallel to and 100 ft. dist. from the left bank of the North Umpqua River.

Over level land, through moderate timber and light undergrowth.

7.42

Point for angle point No. 5, 100 ft. normal dist. from the left bank of the North Umpqua River, in a gravelled road, 15 lks. wide, in curve, bears N. 30° E. to S. 60° W.

Set an iron post, 28 ins. long, 2½ ins. diam., 33 ins. in the ground, the top 5 ins. below surface of road, with brass cap mkd.



from which

A fir, 16 ins. diam., bears N. 7° E., 140½ lks. dist., mkd. AP5 S9 BT.

A fir, 23 ins. diam., bears West, 147 lks. dist., mkd. AP5 S9 BT.


Thence

N. 50° 00' E., parallel to and 100 ft. dist. from the left bank of the North Umpqua River.

5.81

Point for angle point No. 6, 100 ft. normal dist. from the left bank of the North Umpqua River.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.



from which