

Segregation Survey of Certain Lands in SE $\frac{1}{4}$ , Section 9,  
T. 26 S., R. 3 W., Willamette Meridian, Oregon

## CHAINS

A fir, 23 ins. diam., bears N. 21° E., 79 lks. dist., mkd. AP6 S9 BT.

A fir, 15 ins. diam., bears N. 2° W., 58 lks. dist., mkd. AP6 S9 BT.


Thence

N. 29° 45' E., parallel to and 100 ft. dist. from the left bank of the North Umpqua River.

2.50 Gravelled road, 15 lks. wide, in curve, bears N. 60° E. to S. 60° W.

7.87 Point for angle point No. 7, 100 ft. normal dist. from the left bank of the North Umpqua River.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.



from which

A double trunked tan oak, 35 ins. diam., bears N. 66° E., 19 lks. dist., mkd. AP7 S9 BT.

A fir, 20 ins. diam., bears N. 39° W., 37 lks. dist., mkd. AP7 S9 BT.


Thence

North, parallel to and 100 ft. dist. from the left bank of the North Umpqua River.

3.14 Angle point No. 8, 100 ft. normal dist. from the left bank of the North Umpqua River, established and recorded by Arthur Boyer, Registered Engineer, No. 1581, in 1942, monumented with an iron pipe, ½ in. diam., firmly set, projecting 4 ins. above ground.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.



from which

A black oak, 15 ins. diam., bears N. 66° W., 71 lks. dist., mkd. AP8 S9 BT.

A fir, 15 ins. diam., bears N. 9° W., 39 lks. dist., mkd. AP8 S9 BT.