

15927

Segregation Survey of Certain Lands in SE $\frac{1}{4}$, Section 9,
T. 26 S., R. 3 W., Willamette Meridian, Oregon

CHAINS

Deposit iron pipe alongside iron post.

Thence

N. 33° 42' E.

2.74

Angle point No. 9, established and recorded by Arthur Boyer, Registered Engineer, No. 1581, in 1942, monumented with an iron pipe, $\frac{1}{2}$ in. diam., firmly set, projecting 6 ins. above ground.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

AP 9

T 26 S
R 3 W
S 9
1972

from which

A fir, 15 ins. diam., bears N. 6° E., 65 lks. dist., mkd. AP9 S9 BT.

A fir, 17 ins. diam., bears N. 10° W., 54 lks. dist., mkd. AP9 S9 BT.

Deposit iron pipe alongside iron post.

Thence

N. 40° 50' E.

2.10

Angle point No. 10, established and recorded by Arthur Boyer, Registered Engineer, No. 1581, in 1942, monumented with an iron pipe, $\frac{1}{2}$ in. diam., firmly set, projecting 6 ins. above ground.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

AP 10

T 26 S R 3 W
S 9
1972

from which

A ponderosa pine, 10 ins. diam., bears N. 88° W., 30 lks. dist., mkd. AP10 S9 BT.

A fir, 12 ins. diam., bears N. 7° W., 53 lks. dist., mkd. AP10 S9 BT.

Deposit iron pipe alongside iron post.

Thence

N. 44° 39' E.