

Segregation Survey of Certain Lands in SE $\frac{1}{4}$, Section 9,
T. 26 S., R. 3 W., Willamette Meridian, Oregon

CHAINS
2.35

Angle point No. 11, established and recorded by Arthur Boyer, Registered Engineer, No. 1581, in 1942, monumented with an iron pipe, $\frac{1}{2}$ in. diam., firmly set, projecting 6 ins. above ground.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

AP 11
T 26 S R 3 W
S 9
1972

from which

A cedar, 17 ins. diam., bears S. 70° W., 56 lks. dist., mkd. AP11 S9 BT.

A fir, 6 ins. diam., bears N. 4° W., 55 lks. dist., mkd. AP11 S9 BT.

Deposit iron pipe alongside iron post.

Thence

N. 52° 53' E.

3.81

Angle point No. 12; established and recorded by Arthur Boyer, Registered Engineer, No. 1581, in 1942, monumented with an iron pipe, $\frac{1}{2}$ in. diam., firmly set, projecting 5 ins. above ground.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

AP 12
T 26 S R 3 W
S 9
1972

from which

A cedar, 9 ins. diam., bears N. 38° E., 52 lks. dist., mkd. AP12 S9 BT.

A fir, 22 ins. diam., bears N. 64° W., 69 lks. dist., mkd. AP12 S9 BT.

Deposit iron pipe alongside iron post.

Thence

N. 52° 30' E.

2.25

Point for angle point No. 13, 100 ft. normal dist. from the left bank of the North Umpqua River.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.